

# FlexFlame BFOU(c) 250V S4/S8 Arctic Grade

Fire resistant, flame retardant halogen-free instrumentation cable. Oil & Mud resistant. Cold bend / Cold impact resistant



## BFOU(c) 150/250(300)V

MGT/EPR/EPR/TCWB/EVA

NEK TS 606 Code S4/S8 Arctic Grade

Operating temperature : 90°C  
 Operating Voltage : 150/250(300)V

### Application

Fixed installation for instrumentation, communication, control and alarm systems in both EX- and safe areas, emergency and critical systems where requirement for fire resistance exists. Meets the OIL & MUD resistance requirement in NEK TS 606:2009. Meets the cold bend / cold impact requirement in CSA 22.2 0.3-01 and IEC 60092-350 Clause 8.9 & Annex E at -40°C/-35°C.

### Standards applied

IEC 60092-376 (2003-05)	- Design
IEC 60228 class 2	- Conductor
IEC 60092-351	- Insulation
IEC 60092-359	- Sheath
IEC 60332-1	- Flame Retardant
IEC 60332-3-22	- Flame Retardant
IEC 60331-1, -2, -21	- Fire Resistant
IEC 60754-1,2	- Halogen Free
IEC 61034-1,2	- Low Smoke
CSA 22.2 0.3-01 (-40°C/-35°C) / IEC 60092-350 Annex E (-40°C/-35°C)	- Cold Bend / Cold Impact

### Construction

	Code Letter	
Conductor		Tinned annealed stranded circular copper (STCC), IEC 60228 class 2
Insulation	<b>B</b>	Mica-tape + EP-rubber, IEC 60092-351 (EPR)
Pair / Triple / Quad twisting		Color coded cores twisted together and wrapped with polyester tape. Pairs/Triples are laid up collectively and screened by copper backed polyester tape with tinned copper drain wire. Pairs/triples are identified by numbered tape or by numbers printed directly on the insulated conductors.
Inner covering	<b>F</b>	Flame retardant and halogen-free thermoplastic compound
Tape over inner covering		PET tape
Armour/screen	<b>O</b>	Tinned annealed copper wire braid
Tape over armour/screen		PET tape
Outer sheath	<b>U</b>	Flame retardant, halogen-free, mud and cold bend / cold impact resistant thermoset compound, SHF2 (IEC 60092-359)
Marking text		Eg. "meter" "year" DRAKA 01 BFOU(C) 250V S4/S8 4PAIR 0.75mm <sup>2</sup> FLEX - FLAME IEC 60092-376 IEC 60331-1*) or IEC 60331-2*) IEC 60331-21 IEC 60332-3-22 ARCTIC GRADE Cold bend (-40 deg. C) / Cold impact (-35 deg. C)
Manufacturing unit		DRAKA 01 = Draka Norsk Kabel
Outer sheath colour		Grey or Blue

\*) IEC 60331-1 for cables with an overall diameter exceeding 20 mm and IEC 60331-2 for cables with an overall diameter not exceeding 20 mm

# FlexFlame BFOU(c) 250V S4/S8 Arctic Grade

## Core identification instrumentation cables

Pair - Black - Light Blue

Triple - Black - Light Blue - Brown

Quad - Black - Light Blue - Brown - Grey

## Range and dimensions

Number of elements	No of cores in element	Cross section core, mm <sup>2</sup>	Conductor Diameter, mm	Insulation Thickness, mm	Thickness Inner covering, mm	Diameter inner covering, mm	Diameter Braid Wire, mm	Mechanical cross-section of the braid, mm <sup>2</sup>	Thickness Outer Sheath, mm	Diameter outer sheath, mm	Weight of Cable Approx. (Kg/Km)	Copper content Approx. (kg/km)
2	2	0.75	1.1	0.6	1.1	10.5 ± 0.8	0.3	8.5	1.3	14.5 ± 0.8	340	113
2	2	0.75	1.1	0.6	1.1	10.5 ± 0.8	0.3	8.5	1.3	14.5 ± 0.8	340	113
4	2	0.75	1.1	0.6	1.1	12.5 ± 0.8	0.3	10.2	1.3	16 ± 0.8	440	155
4	2	0.75	1.1	0.6	1.1	12.5 ± 0.8	0.3	10.2	1.3	16 ± 0.8	440	155
8	2	0.75	1.1	0.6	1.1	16.5 ± 0.8	0.3	13.6	1.5	20.5 ± 1	680	240
8	2	0.75	1.1	0.6	1.1	16.5 ± 0.8	0.3	13.6	1.5	20.5 ± 1	680	240
16	2	0.75	1.1	0.6	1.9	22 ± 1	0.3	17.8	1.7	27 ± 1	1180	383
16	2	0.75	1.1	0.6	1.9	22 ± 1	0.3	17.8	1.7	27 ± 1	1180	383
24	2	0.75	1.1	0.6	2.3	27.5 ± 1	0.3	22.9	2	32.5 ± 1.5	1700	536
24	2	0.75	1.1	0.6	2.3	27.5 ± 1	0.3	22.9	2	32.5 ± 1.5	1700	536
2	3	0.75	1.1	0.6	1.1	12 ± 0.8	0.3	10.2	1.3	16 ± 0.8	400	143
2	3	0.75	1.1	0.6	1.1	12 ± 0.8	0.3	10.2	1.3	16 ± 0.8	400	143
4	3	0.75	1.1	0.6	1.1	14 ± 0.8	0.3	11.9	1.4	18 ± 0.8	550	198
4	3	0.75	1.1	0.6	1.1	14 ± 0.8	0.3	11.9	1.4	18 ± 0.8	550	198
8	3	0.75	1.1	0.6	1.1	18.5 ± 0.8	0.3	15.3	1.6	23 ± 1	870	308
8	3	0.75	1.1	0.6	1.1	18.5 ± 0.8	0.3	15.3	1.6	23 ± 1	870	308
16	3	0.75	1.1	0.6	2.1	25.5 ± 1	0.3	20.4	1.8	30.5 ± 1.5	1560	513
16	3	0.75	1.1	0.6	2.1	25.5 ± 1	0.3	20.4	1.8	30.5 ± 1.5	1560	513
24	3	0.75	1.1	0.6	2.5	31.5 ± 1.5	0.4	36.2	2.1	37.5 ± 1.5	2350	822
2	2	1.5	1.6	0.7	1.1	13 ± 0.8	0.3	10.2	1.4	17 ± 0.8	450	162
2	2	1.5	1.6	0.7	1.1	13 ± 0.8	0.3	10.2	1.4	17 ± 0.8	450	162
4	2	1.5	1.6	0.7	1.1	15 ± 0.8	0.3	11.9	1.4	19 ± 0.8	600	234
4	2	1.5	1.6	0.7	1.1	15 ± 0.8	0.3	11.9	1.4	19 ± 0.8	600	234
8	2	1.5	1.6	0.7	1.1	20 ± 1	0.3	17.8	1.7	25 ± 1	990	404
8	2	1.5	1.6	0.7	1.1	20 ± 1	0.3	17.8	1.7	25 ± 1	990	404
12	2	1.5	1.6	0.7	1.4	24 ± 1	0.3	20.4	1.8	29 ± 1	1350	540
16	2	1.5	1.6	0.7	1.9	27 ± 1	0.3	22.9	1.9	32 ± 1.5	1740	677
16	2	1.5	1.6	0.7	1.9	27 ± 1	0.3	22.9	1.9	32 ± 1.5	1740	677
24	2	1.5	1.6	0.7	2.3	33.5 ± 1.5	0.4	36.2	2.2	39.5 ± 1.5	2610	1030
24	2	1.5	1.6	0.7	2.3	33.5 ± 1.5	0.4	36.2	2.2	39.5 ± 1.5	2610	1030
2	3	1.5	1.6	0.7	1.1	14.5 ± 0.8	0.3	11.9	1.4	18.5 ± 0.8	540	207
2	3	1.5	1.6	0.7	1.1	14.5 ± 0.8	0.3	11.9	1.4	18.5 ± 0.8	540	207
4	3	1.5	1.6	0.7	1.1	17 ± 0.8	0.3	13.6	1.5	21 ± 1	760	307
4	3	1.5	1.6	0.7	1.1	17 ± 0.8	0.3	13.6	1.5	21 ± 1	760	307
8	3	1.5	1.6	0.7	1.1	22.5 ± 1	0.3	17.8	1.8	27.5 ± 1	1270	517
8	3	1.5	1.6	0.7	1.1	22.5 ± 1	0.3	17.8	1.8	27.5 ± 1	1270	517
12	3	1.5	1.6	0.7	1.4	27 ± 1	0.3	22.9	1.9	32.5 ± 1.5	1760	736
16	3	1.5	1.6	0.7	2.3	31.5 ± 1.5	0.4	36.2	2.1	37.5 ± 1.5	2540	1034
16	3	1.5	1.6	0.7	2.3	31.5 ± 1.5	0.4	36.2	2.1	37.5 ± 1.5	2540	1034
24	3	1.5	1.6	0.7	2.7	38.5 ± 1.5	0.4	40.7	2.4	45 ± 2	3560	1421
2	2	2.5	2	0.7	1.1	14 ± 0.8	0.3	11.9	1.4	18 ± 0.8	530	217
4	2	2.5	2	0.7	1.1	16.5 ± 0.8	0.3	13.6	1.5	20.5 ± 1	740	325
8	2	2.5	2	0.7	1.1	22 ± 1	0.3	17.8	1.8	27 ± 1	1230	551
16	2	2.5	2	0.9	2.3	33 ± 1.5	0.4	31.7	2.1	39 ± 1.5	2590	1054
24	2	2.5	2	0.9	2.7	41 ± 2	0.4	40.7	2.4	47.5 ± 2	3760	1511
8	3	2.5	2	0.7	1.1	25 ± 1	0.3	20.4	1.9	30 ± 1.5	1620	762
16	3	2.5	2	0.9	2.6	38.5 ± 1.5	0.4	36.2	2.3	44.5 ± 2	3550	1473

Subject to change without prior notice

# FlexFlame BFOU(c) 250V S4/S8 Arctic Grade

## Electrical values instrumentation cables

Type	Capacitance, approx. (nF/km)	Inductance, approx. (mH/km)	Resistance at 20°C, max. (Ohm/km)	L/R ratio, (microH/Ohm)
Unshielded pair 0,75 mm <sup>2</sup>	100	0,67	26,3	12,7
Unshielded triple 0,75 mm <sup>2</sup>	100	0,67	26,3	12,7
Unshielded pair 1,5 mm <sup>2</sup>	110	0,63	12,9	24,4
Unshielded triple 1,5 mm <sup>2</sup>	110	0,63	12,9	24,4
Unshielded pair 2,5 mm <sup>2</sup>	125	0,59	8,02	36,8
Unshielded triple 2,5 mm <sup>2</sup>	125	0,59	8,02	36,8
Unshielded 16 and 24 pair 2,5 mm <sup>2</sup>	95	0,66	8,02	36,8
Unshielded 12, 16 and 24 triple 2,5 mm <sup>2</sup>	95	0,66	8,02	36,8

## Ordering information

Part number	Description	Sheath Colour	Stock item	EAN No. DNK	EL No.
813806	BFOU(C) 2PAIR 0.75mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528138061	-
813807	BFOU(C) 2PAIR 0.75mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528138078	-
813818	BFOU(C) 4PAIR 0.75mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528138184	-
813819	BFOU(C) 4PAIR 0.75mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528138191	-
813830	BFOU(C) 8PAIR 0.75mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528138306	-
813831	BFOU(C) 8PAIR 0.75mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528138313	-
813842	BFOU(C) 16PAIR 0.75mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528138429	-
813843	BFOU(C) 16PAIR 0.75mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528138436	-
813848	BFOU(C) 24PAIR 0.75mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528138481	-
813849	BFOU(C) 24PAIR 0.75mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528138498	-
813866	BFOU(C) 2TRIP 0.75mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528138665	-
813867	BFOU(C) 2TRIP 0.75mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528138672	-
813878	BFOU(C) 4TRIP 0.75mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528138788	-
813879	BFOU(C) 4TRIP 0.75mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528138795	-
813890	BFOU(C) 8TRIP 0.75mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528138900	-
813891	BFOU(C) 8TRIP 0.75mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528138917	-
813902	BFOU(C) 16TRIP 0.75mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528139020	-
813903	BFOU(C) 16TRIP 0.75mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528139037	-
813908	BFOU(C) 24TRIP 0.75mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528139082	-
814006	BFOU(C) 2PAIR 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528140064	-
814007	BFOU(C) 2PAIR 1.5mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528140071	-
814018	BFOU(C) 4PAIR 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528140187	-
814019	BFOU(C) 4PAIR 1.5mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528140194	-
814030	BFOU(C) 8PAIR 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528140309	-
814031	BFOU(C) 8PAIR 1.5mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528140316	-
814036	BFOU(C) 12PAIR 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528140361	-
814042	BFOU(C) 16PAIR 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528140422	-
814043	BFOU(C) 16PAIR 1.5mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528140439	-
814048	BFOU(C) 24PAIR 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528140484	-
814049	BFOU(C) 24PAIR 1.5mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528140491	-
814066	BFOU(C) 2TRIP 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528140668	-
814067	BFOU(C) 2TRIP 1.5mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528140675	-
814078	BFOU(C) 4TRIP 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528140781	-
814079	BFOU(C) 4TRIP 1.5mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528140798	-
814090	BFOU(C) 8TRIP 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528140903	-
814091	BFOU(C) 8TRIP 1.5mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528140910	-
814096	BFOU(C) 12TRIP 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528140965	-
814102	BFOU(C) 16TRIP 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528141023	-
814103	BFOU(C) 16TRIP 1.5mm <sup>2</sup> S4/S8 Cold	BLUE	-	7021528141030	-
814108	BFOU(C) 24TRIP 1.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528141085	-
814206	BFOU(C) 2PAIR 2.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528142068	-
814218	BFOU(C) 4PAIR 2.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528142181	-
814230	BFOU(C) 8PAIR 2.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528142303	-
814242	BFOU(C) 16PAIR 2.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528142426	-
814248	BFOU(C) 24PAIR 2.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528142488	-

Subject to change without prior notice

## FlexFlame BFOU(c) 250V S4/S8 Arctic Grade

Part number	Description	Sheath Colour	Stock item	EAN No. DNK	EL No.
814290	BFOU(C) 8TRIP 2.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528142907	-
814302	BFOU(C) 16TRIP 2.5mm <sup>2</sup> S4/S8 Cold	GREY	-	7021528143027	-

### Installation recommendations

Minimum Bending Radius during Installation	Minimum Bending Radius Fixed Installed	Maximum Tensile Load During Installation	Minimum Installation Temperature
8 x D	6 x D	50 N /mm <sup>2</sup>	-40°C